

TC1

series



Product Segments

Care Motion

Voltage

Built-in transformer type

Maximum output

Plug support

Number of actuators

Color

IP rating

Certificate

100V AC, 120V AC, 230V AC,

or 100~240V AC (SMPS) EI, Toroidal, or SMPS

29V DC, 6.0A

EU, USA, AUS, UK, JPN, or customized

1~4


black or grey

IP54 or IP66

IEC60601-1, ES/UL60601-1, and FCC

Drawing

Standard Dimension (mm)



Terms of Use

The user is responsible for determining the suitability of TiMOTION products for a specific application.

Due to continuous development in order to improve our products, TiMOTION products are subject to frequent modifications and changes without prior notice.

TiMOTION reserves the right to discontinue the sale of any products displayed on its website or listed in its catalogue or other written materials drawn up by TiMOTION.



TC1 Ordering Key



				Version: 20140519-H
Voltage	1 = 100V AC	2 = 120V AC	3 = 230V AC	4 = 100~240V AC (SMPS)
Plug	1 = EU	3 = AUS	5 = JPN	
	2 = USA	4 = UK	A = Others	
Number of Actuators	1 = 1	2 = 2	3 = 3	4 = 4
Color	1 = Black		2 = Grey (Pantone 428C)	
Cable Length	1 = Straight, 2000mm	2 = Straight, 4000mm	A = Customized	
IP Protection	1 = Without	2 = IP54	3 = IP66	
Fixation	1 = On the actuator (TA1)		4 = On the bed frame with a bracket	
	2 = On the bed frame		5 = On the bed frame with brass spacers	
	3 = On the actuator (TA7)		insert in the cover	
Grounding Function	0 = Without		1 = With	